



865 West 2600 South, Salt Lake City, UT 84119
Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

HYDROBLASTERS - HYDROKLEEN - HYDROPAD

www.hydroblaster.com

Model 30/200E **High volume De-Muck System**

GENERAL SPECIFICATIONS AND USE

Heavy mud and dirt accumulations can be removed quickly with the Hydroblaster De-mucking system. At a rate of 30 gallons per minute water is forced through an adjustable nozzle at 200 PSI allowing the operator to use a gentle fan or direct stream of water for heavy mud accumulations wash down. Dozers, front end loaders, back hoes and all heavy equipment can be cleaned quickly with this system.

Standard equipment:

- 500 Gallon Water Holding Tank
- Skid Mounted With Fork Lift Slots
- Pressure Gauge
- Low Intake Water Protection System
- Automatic Fresh Water Makeup And Pump Bypass System

Options:

Electrical: Power & Controls

- 2BQ946 7.5 HP, 208-230/115 Volt, 3 Phase, Contactor & Overload
2BQ944 7.5 HP, 208-230/115 Volt, 1 Phase, Contactor & Overload
2IS285 7.5 HP, 460 Volt, 3 Phase, Contactor & Overload

Remote Options

- 2OQ321 Remote On/Off, NEMA 4x Enclosure

Inlet Control Options

- 2KE165 Float Switch, SPST, NC, ½ HP, 115 Volt

Inlet Fittings/Plumbing

- 2KL239 Single Inlet Feed, 1.5" FPT
2KE169 Dual Inlet Feed, 1.5" FPT

Tank Discharge Options

- 2RB956 No Discharge
2SJ296 Sump Pump Discharge, 1.5", 1/3HP, 115 Volt
1WV698 Polishing Loop W/Pump, (Requires Cmafu-2)

Drain Line Control Valves

- 1WV697 Sludge Drain, Manual Valve, 1.5"
2QY923 Sludge Drain, W/Motorized Ball Valve, (Requires a System W/Logic Control)

Wash Hose Options

- 2BR955 Discharge Hose, 50'
2BR957 Discharge Hose, 100'

Hose Reel Options

- 2CA042 No Hose Reel
2BR958 Hose Reel, Manual, Mounted, Small Stand
2CA041 Hose Reel, Manual, Mounted, Large Stand
2QY927 Reel Mount, Floor Plate
2QY926 Reel Mount, Side Plate, Hydropad



Quality Assured Firm
ISO 9001 Certified



Certified Systems Available