

**5/3000EHGV-M1 Hydroblaster™**  
**5/3000EHOV-M1 Hydroblaster™**  
**M Series**



<b>PART #</b>	<b>5/3000</b>
<b>VOLUME (GPM)</b>	5
<b>PRESSURE (PSI)</b>	3000
<b>BTU (PER HR. X 1000)</b>	400
<b>EXHAUST STACK (DIA)</b>	10"
<b>COIL SPEC (SCH 80)</b>	1/2"
<b>WATER FLOAT TANK (GAL)</b>	2
<b>ELECTRIC MOTOR (HP)</b>	10
<b>VOLTAGE CODE<sup>1</sup></b>	C, D
<b>AMPERAGE</b>	29, 15
<b>LENGTH (INCHES)</b>	45
<b>HEIGHT (W/LEGS)</b>	55
<b>WIDTH</b>	34
<b>WEIGHT (LBS)</b>	695



**Standard Features:**

- EHG – Gas fired heat
- EHOV – Oil fired heat
- Auto pilot ignition
- Heavy duty electric motor
- Hour Meter
- Schedule 80 steel coil
- Belt drive
- Float tank
- Full stainless steel equipment covers
- Trigger gun with insulated variable pressure wand
- 0, 15, 25 & 40 degree nozzles
- Downstream chemical injection
- Remote On/Off With Explosion Proof Enclosure
- Soap foaming system that provides adjustable foam delivery
- Foam delivery system has pump and foam air adjustments
- Retractable reel for foaming soap system
- 100' soap hose
- High Pressure reel for hot high pressure water
- 100' hose rated 3000 PSI
- Remote start stop is 24 volt control voltage

