

Solvent Recycling Tank Model SRT

The ultimate filtration/recycling system for reclaiming ink wash systems

Air Driven Pump: For safety! Requires less than 10 CFM and 100 PSI to operate. Operating pressure of 20 to 40 PSI.

All Stainless Steel: control panel as well as fluid tank and sump housing.

Portable: 4 swivel casters make the system easy to move for service and fluid replacement.



Sump: A 20 micron filter bag collects solids for disposal. Also a built in weir maintains solids in this compartment where system cleaning is centralized.

Ink Wash: Supply hose connects directly to ink wash out brush.

Dimensions: 25"H x 16"W x 33 1/2"L

Utilities Required: Shop air (100 PSI and 10 CFM)

Recycle Ink Wash!

- Air powered diaphragm pump will handle most fluids
- SRT is available in 20 gallon and 50 gallon sizes
- No electric hook up required
- Bag filter is simple to change
- Stainless steel construction eliminates corrosion problems

IMPORTANT: SOME SOLVENTS MAY NOT BE ACCEPTABLE TO OPERATE WITHIN THE SRT. CONSULT HYDRO ENGINEERING INC FOR CHEMICAL COMPATIBILITY.

1. Specifications are effective Oct 1, 2003
2. Specifications are subject to change without notice.



865 West 2600 South, Salt Lake City, UT 84119
Phone 800-247-8424 or 801-972-1181 Fax 801-972-3265

HYDROBLASTERS - HYDROKLEEN - HYDROPAD

www.hydroblaster.com